

# HUNTER 600

VEGNIK



## SOIL AERATOR WITH HIGH CAPACITY



- ✓ Solidly built machine with high capacity
- ✓ Constant working depth
- ✓ Low power requirement

## SOLIDLY BUILT HIGH CAPACITY MACHINE

The Hunter 600 is characterized by its large working width of no less than 6.0 meters. While the transport width is within 3 meters. The framework is solidly built. You can mount the machine in several positions to ensure that the tractor's lower links can always be ideally positioned which leads to a perfect traction point.

## CONSTANT WORKING DEPTH

The machine is very stable and works on a constant working depth because of the wide supporting wheels. The curved tine lifts the ground and aerates the soil perfectly without disturbing the top layer. After using the Hunter 600 the ground remains possible to drive on for later tillage operations because the top layer remains virtually undisturbed.

## LOW POWER REQUIREMENT

Because of the tines are mounted in a V-shape, the ground has more space to break. As a result of this design, the machine requires less power and has a low wear and tear.



## BENEFITS

- ✓ High capacity with a low power requirement
- ✓ The tractor has a lot grip because of the perfect pull line
- ✓ Stable machine because of wide supporting wheels
- ✓ Tines can be assembled at different distances
- ✓ Perfect finishing touch with width signs and LED lights

## OPTIONS

- ✓ 10 subsoiler tines at 580mm c.o.h.

## STANDARD PROPERTIES

Work width: 3,0 – 4,5 or 6,0 mtr  
 Transport width: 2,96 mtr  
 Weight: 2060 kg  
 Tine distance subsoiler c.o.h.: 580 or 750 mm  
 Working depth: 25 - 50 cm  
 Tines overload protection by shear bolts  
 Hydraulic folding system  
 Level position indicator

### TIP!

SEE HOW THE  
 HUNTER 600  
 WORKS?  
 SCAN THE QR-CODE:

