

SUBSOILER

VEGNIEK



THE SUBSOILER WITH HYDRAULICALLY EXTENDABLE TINES



- ✓ Short mounting length
- ✓ Robust main frame
- ✓ Can be used in various ways

SHORT MOUNTING LENGTH

Vegniek subsoilers are robust machines with a short mounting length. Due to the hydraulically extendable tines, a hydraulic lifting device is not required and the next machine (e.g. power harrow) can be mounted very short. The great advantage of the very short mounting length is that the tractor's lifting capacity is not limited. The open constructed main frame makes it possible to use a PTO-driven following machine.

CAN BE USES IN VARIOUS WAYS

The Vegniek subsoiler can be fitted with both fixed tines and tines whose spacing can be adjusted. This allows you to aerate the soil in any situation, with the desired tine spacing. The modular built Vegniek subsoiler is available in various versions. You can choose the type of tine, the number of tines and the working width.



BENEFITS

- ✓ Short mounting length
- ✓ Tines can be hydraulically extended
- ✓ Can be used in combination with many other machinery
- ✓ Robust construction
- ✓ Many options for tines and tine spacings

STANDARD

- ✓ Heavy main frame with CatIII lifting points
- ✓ Transport width 3.3 metres
- ✓ Two hydraulically extendable tines
- ✓ Various tine spacings possible
- ✓ Working depth adjustable to approx. 45 cm
- ✓ Tines overload protection by shear bolts

OPTIONS

- ✓ Extra tines
- ✓ Set of width signs
- ✓ Set of CatIII link hooks for mounting e.g. harrow
- ✓ Tow bar K80

STANDARD PROPERTIES

Working width: 3 mtr
 Transport width: 3,3 mtr
 Number of tines: 2
 Weight: 750 kg
 Tines overload protection by shear bolts

TIP!

SEE HOW
THE SUBSOILER
WORKS?
SCAN THE QR-CODE:

